



常规型号电池 充电器参数表

型号	每组只数 (只/组)	充电器参数			
		充电电流(A)	最高电压(V)	浮充电压(V)	转换电流(A)
6-DZM-12	4	1.8-2.2	58.6-59	54.8-55.2	0.38-0.43
	5	1.8-2.2	73.3-73.6	68.5-69	0.38-0.43
	6	1.8-2.2	88-88.4	82.3-82.7	0.38-0.43
6-DZM-20	4	2.3-2.7	58.6-59	54.8-55.2	0.55-0.60
	5	2.3-2.8	73.3-73.6	68.5-69	0.55-0.61
	6	2.3-2.9	88-88.4	82.3-82.7	0.55-0.62
6-EVF-32	4	4.5-5.0	58.6-59	54.8-55.2	0.6-0.65
	5	4.5-5.0	73.3-73.6	68.5-69	0.6-0.65
	6	4.5-5.0	88-88.4	82.3-82.7	0.6-0.65
6-EVF-38	4	5.0-5.5	58.6-59	54.8-55.2	0.65-0.70
	5	5.0-5.5	73.3-73.6	68.5-69	0.65-0.70
	6	5.0-5.5	88-88.4	82.3-82.7	0.65-0.70
6-EVF-40	4	5.5-6.0	58.6-59	54.8-55.2	0.65-0.70
	5	5.5-6.0	73.3-73.6	68.5-69	0.65-0.70
	6	5.5-6.0	88-88.4	82.3-82.7	0.65-0.70
6-EVF-45	4	6.0-6.5	58.6-59	54.8-55.2	0.7-0.75
	5	6.0-6.5	73.3-73.6	68.5-69	0.7-0.75
	6	6.0-6.5	88-88.4	82.3-82.7	0.7-0.75
6-EVF-50	4	7.0-7.5	58.6-59	54.8-55.2	0.75-0.8
	5	7.0-7.5	73.3-73.6	68.5-69	0.75-0.8
	6	7.0-7.5	88-88.4	82.3-82.7	0.75-0.8
6-EVF-56	4	7.5-8.0	58.6-59	54.8-55.2	0.75-0.8
	5	7.5-8.0	73.3-73.6	68.5-69	0.75-0.8
	6	7.5-8.0	88-88.4	82.3-82.7	0.75-0.8

